

**AMENDMENTS TO THE CLAIMS**

Claim 1 (Currently amended): A spinal fixation device, comprising:

a first elongate member having a female connector with opposed arms  
and a second elongate member having a male connector adapted to mate to the  
female connector, the first and second elongate members coupled to one another  
such that the first and second elongate members are angularly adjustable relative  
to one another; and

a mating element adapted to extend through the male and female  
connectors; and

a fastening element ~~locking mechanism~~ adapted to mate to at least one of  
the male and female connectors to lock the elongate members in a fixed position  
relative to one another ~~independent of a bone anchor~~

wherein at least one of the first and second elongate members is a spinal  
fixation rod.

Claim 2 (Original): The spinal fixation device of claim 1, wherein angular adjustment of  
each elongate member is limited to a single plane.

Claim 3-6 (Cancelled).

Claim 7 (Currently Amended): The spinal fixation device of claim 1, wherein the ~~other~~  
~~of the~~ first and second elongate members is each comprise a spinal fixation rod.

Claim 8 (Currently Amended): The spinal fixation device of claim 1, wherein ~~the other~~  
~~of the first and second elongate~~ member members is a spinal fixation plate and

the second elongate member is a spinal fixation rod.

Claim 9 (Original): The spinal fixation device of claim 1, wherein the first elongate member is a spinal fixation rod and second elongate member is a spinal fixation plate.

Claim 10 (Original): The spinal fixation device of claim 1, wherein the first elongate member has a diameter that is different than a diameter of the second elongate member.

Claim 11-12 (Cancelled).

Claim 13 (Previously Presented): The spinal fixation device of claim 1, wherein the opposed arms define a recess therebetween for receiving the male connector.

Claim 14 (Currently Amended): The spinal fixation device of claim 1, further comprising a bore extending through the opposed arms on the female connector and through the male connector, and the ~~a central~~-mating element extending through the bore for mating the male and female connectors to one another.

Claim 15 (Currently Amended): The spinal fixation device of claim 14, wherein the ~~central~~-mating element comprises a cylindrical member, the cylindrical member being adapted to allow at least one of the first and second elongate members to rotate thereabout.

Claim 16 (Original): The spinal fixation device of claim 15, wherein the cylindrical member is fixedly coupled to a portion of the female connector, and the male connector is free to rotate about the cylindrical member.

Claim 17 (Currently Amended): The spinal fixation device of claim 16, wherein the fastening element ~~locking mechanism~~ is effective to engage the cylindrical member to prevent movement of the male connector relative to the female connector.

Claim 18 (Currently Amended): The spinal fixation device of claim 17, wherein the fastening element ~~locking mechanism~~ comprises a slot extending through the male connector such that the male connector is in the form of a clamp, and wherein the ~~locking mechanism further comprises a fastening element~~ is adapted to engage the male connector to clamp the cylindrical member within the bore.

Claim 19 (Original): The spinal fixation device of claim 18, wherein the fastening element comprises a threaded member.

Claim 20 (Previously Presented): The spinal fixation device of claim 1, wherein the female connector and male connector of the first and second elongate members rotate about a central axis extending substantially perpendicular to an axis of each first and second elongate members.

Claim 21-41 (Canceled).

Claim 42 (Currently amended): A spinal fixation device, comprising:

first and second elongate members, each having a connecting feature formed on a terminal end thereof, the connecting features being coupled to one another such that the first and second elongate members are angularly adjustable relative to one another along a plane;

a mating element adapted to extend through the first and second elongate members; and

a fastening element ~~locking mechanism~~ adapted to extend into at least one of the connecting features along an axis that is substantially parallel to the plane to lock the first and second elongate members in a fixed position relative to one another

wherein at least one of the first and second elongate members is a spinal fixation rod.

Claim 43 (Currently Amended): A spinal fixation device, comprising:

first and second elongate members coupled to one another such that the first and second elongate members are angularly adjustable relative to one another, the angular adjustability of each elongate member being limited to a single plane;

a mating element adapted to extend through the first and second elongate members; and

a fastening element ~~locking mechanism~~ adapted to lock the elongate members in a fixed position relative to one another, the locking mechanism extending along an axis that is substantially parallel to the single plane of angular adjustability of each elongate member

wherein at least one of the first and second elongate members is a spinal fixation rod.

Claim 44-45 (Cancelled).

Claim 46 (Currently amended): A spinal fixation device, comprising:

a first elongate element having a clamping mechanism formed on a terminal end thereof;

a second elongate element having a terminal end adapted to be received by the clamping mechanism on the first elongate element; and

a fastening element ~~locking mechanism~~ adapted to engage and close lock the clamping mechanism such that the second elongate member can be maintained in a fixed position relative to the first elongate member

wherein at least one of the first and second elongate members is a spinal fixation rod.

Claim 47 (Original): The spinal fixation device of claim 46, wherein the first elongate element has a diameter different from a diameter of the second elongate element.

Claim 48 (Original): The spinal fixation device of claim 46, wherein the first elongate element has a diameter that is the same as a diameter of the second elongate element.

Claim 49 (Original): The spinal fixation device of claim 46, wherein the terminal end of the second elongate element is positioned at an angle relative to a longitudinal axis of the second elongate element.

Claim 50 (Original): The spinal fixation device of claim 49, wherein the angle is about 90°.

Claim 51-59 (Cancelled)